





# SVEZA INTERIOR BIRCH PLYWOOD



# SVEZA INTERIOR BIRCH PLYWOOD

SVEZA Interior Birch Plywood is easy to process and goes well together with finish materials. This type of plywood is ideal for indoor use.

## Key benefits

-  **Durable and wear resistant**
-  **Hard surface**
-  **Higher water-resistance**
-  **Comes in a variety of thicknesses and sizes**

## Technical specifications

Standard sizes, length x width, mm (ft)	1525x1525 (5x5) 2440/2500x1500/1525 (8x5)
Thickness, mm	3-25
Plywood grade	I (B, S), II (BB), III (CP), IV (C)
Surface type	Outer layers sanded (S2S), one side sanded (S1S), unsanded (NS)
Formaldehyde emission class	E1
Waterproofness	Normal
Density, kg/m <sup>3</sup>	640-700
Moisture content, %	5-14
Edge sealing	—
Plywood is produced under STO 00255177-001-2013 "General purpose plywood with birch face veneers."*	

## Strength specifications

Subject		Thickness, mm	Index
Static bending strength, N/mm <sup>2</sup> , not less	along the outer layer grain	9-40	45
	across the outer layer grain		30
Strength in tension along the grain, N/mm <sup>2</sup> , not less		3-8	30
Modulus of elasticity in static bending, N/mm <sup>2</sup> , not less	along the grain	9-40	5000
	across the grain		3000

\*For STO 00255177-001-2013, visit "Certificates" section of [www.sveza.com](http://www.sveza.com) website.

Proudly Distributed By



- US: 888-826-5528
- CAN: 844-365-6995
- [hardwoods-inc.com](http://hardwoods-inc.com)