

| <b>Echo Wood Specification</b> |  |
|--------------------------------|--|
| <b>Item</b>                    | <b>Vendor</b>  |
| <b>DESCRIPTION</b>             | O2 BAMBOO Plywood  |
| <b>NAME</b>                    | [VG Carbonized]  |
| <b>STYLE#</b>                  | [SCAV-0100]  |
| <b>FSC Certified</b>           | <b>Yes</b>   |
| <b>LOCATION</b>                | See drawings for details   |
| <b>Number of Plys</b>          | <b>1-ply or 3-ply</b>  |
| <b>COLOR</b>                   | [Light Brown]  |
| <b>GRAIN - CUT</b>             | [straight]   |
| <b>THICKNESS</b>               | 0.6mm  |
| <b>UV LIGHT RESISTANCE</b>     | UV inhibitor must be used in finish  |
| <b>FINISH</b>                  | [Insert finish] Clear lacquer 30% sheen  |
| <b>GLUE</b>                    | No Added Urea Formaldehyde   |
| <b>ECHO WOOD SPECIFICATION</b> | Face veneer or panel to match architect's sample. Bamboo pole shall be at least 5 years old and cut from mature Moso Bamboo plants. Bamboo panels and veneer must come from the highest AA grade Bamboo. Continuous inspection throughout the manufacturing process is required. |
| <b>NOTES</b>                   | <b>Veneer to match architects sample. No substitutions</b>   |